



**Item P95-0012**

**.300 Head Drive Pins**

Drive pins with a .300 diameter head are designed for permanently fastening a fixture to concrete, some types of masonry and A36 structural steel. Drive pins are manufactured with a 0.145" diameter shank in various lengths. Knurled shank designs are available to increase performance in steel base materials. A plastic flute is mounted over the point to retain the drive pin in the fastener guide of the tool providing guidance during the driving operation.

Item	Description	Attributes
95-0012		Shank Length: 1/2" (knurled) Std. Box: 100 Head Dia.: .300 Shank Dia.: .145
15-0411		Shank Length: 5/8" (knurled) Std. Box: 100 Head Dia.: .300 Shank Dia.: .145
15-0412		Shank Length: 3/4" Std. Box: 100 Head Dia.: .300 Shank Dia.: .145
15-0413		Shank Length: 1" Std. Box: 100 Head Dia.: .300 Shank Dia.: .145
15-0414		Shank Length: 1 1/4" Std. Box: 100 Head Dia.: .300 Shank Dia.: .145
15-0415		Shank Length: 1 1/2" Std. Box: 100 Head Dia.: .300 Shank Dia.: .145
15-0416		Shank Length: 2" Std. Box: 100 Head Dia.: .300 Shank Dia.: .145
95-0040		Shank Length: 2 1/4" Std. Box: 100 Head Dia.: .300 Shank Dia.: .145
15-0417		Shank Length: 2 1/2" Std. Box: 100 Head Dia.: .300 Shank Dia.: .145
15-0418		Shank Length: 3" Std. Box: 100 Head Dia.: .300 Shank Dia.: .145