



Item P99-8133

TriggerFoam Pro™ Fireblock

PRODUCT DESCRIPTION

TriggerFoam Pro™ FireBlock is a professional grade, gun applied, polyurethane foam sealant designed to effectively block the spread of smoke and flame in Type V **residential** construction. It is more cost effective than fiberglass and caulks used for this purpose. **NOT A FIRESTOP**. Adheres to wood, metal, masonry and concrete. Seals gaps and joints, insulates, stops air infiltration and saves time and money. Ideal for use around pipes, wires and ductwork.

APPLICATIONS

Dispenses through a special gun that allows the user to control the flow rate and diameter of the bead, allowing precise placement of the foam. Voids should be filled approximately 30-40% to allow for the final expansion of the foam. Recommended curing time is 24 hours prior to scraping or painting.

TYPICAL USES

Insulating

• Floor / wall joints • Electrical junction boxes • Attics • Refrigeration units and pipes • Air conditioning systems

Filling

• Breaches in walls • Pipe penetrations in non-fire-rated walls • Voids in concrete forms • Underground utility ductwork • Sound dampening

| Item | Description | Attributes |
|---------|-------------|---|
| 99-8133 | | Size: TriggerFoam Pro Fireblock 29 oz. Std Box: 12 |