



TOOLS & EQUIPMENT ■ SUPPLIES ■ SAFETY PRODUCTS ■ TOOL REPAIR ■ RENTALS

Item P11-6140

Wilton Carriage Clamps

High tensile ductile alloy casting. Hardened steel spindle. Patented Perma-Pads® are guaranteed never to come off.

| Item | Description | Attributes |
|---------|-------------|--|
| 11-6140 | | Capacity: 0 - 2 1/2" Throat Depth: 1 3/4" Spindle Diameter: 1/2" Minimum Proof Test Lbs.: 1,100 |
| 11-6141 | | Capacity: 0 - 3" Throat Depth: 1 7/8" Spindle Diameter: 1/2" Minimum Proof Test Lbs.: 1,800 |
| 11-6142 | | Capacity: 0 - 4" Throat Depth: 2 1/16" Spindle Diameter: 5/8" Minimum Proof Test Lbs.: 2,150 |
| 11-6143 | | Capacity: 0 - 6" Throat Depth: 2 3/4" Spindle Diameter: 5/8" Minimum Proof Test Lbs.: 2,450 |
| 11-6144 | | Capacity: 0 - 8" Throat Depth: 3 1/4" Spindle Diameter: 3/4" Minimum Proof Test Lbs.: 2,750 |
| 11-6145 | | Capacity: 0 - 10" Throat Depth: 3 5/8" Spindle Diameter: 7/8" Minimum Proof Test Lbs.: 2,850 |
| 11-6146 | | Capacity: 0 - 12" Throat Depth: 3 5/8" Spindle Diameter: 7/8" Minimum Proof Test Lbs.: 2,850 |